



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	VO	Contrast adjust
4	A0	H: Command; L:Data
5	/WR	Data write
6	/RD	Data read
7-14	D0-D7	DATA BUS
15	/RST	Reset signal
16	/CS	Chip select for RA8803.
17	BUSY	Busy signal
18	VEE	Internal negative power output
19	A	Backlight power supply(+5V)
20	K	Backlight power supply(-)

**NOTES:**

1. DISPLAY TYPE: STN, BLUE
2. POLARIZER TYPE: TRANSMISSIVE, NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/240DUTY, 1/17BIAS
8. CONTROLLER: RA8806
9. BACKLIGHT TYPE: WHITE,LED
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

<p><b>WAYING WAYING (HONGKONG) SHARES LIMITED</b></p>		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM320240E3	VERSION:	A
APPROVE:		SHEET:	1 OF 1	DATE:	2009-05-13
Unspecified tolerances are ±0.3					